



MICROCEMENT SYSTEMS

Decorative microcement with high mechanical strength in a wide range of colors and styles

We build together.

We build together
for a better living.



THRAKON

**Welcome to a world full of high quality,
aesthetics and excellent service...
in the world of THRAKON!**

The real experience of building materials and premium colors. Utilizing long-term experience and know-how, THRAKON is one of the largest research and production companies in the building materials, paints and varnishes industry. THRAKON has the ability to provide integrated services and solutions for a wide range of applications.

BRANDS

THRAKON has an active presence in the market with the following leading brands.

CLIMAPLUS

STATUS

DECOR

ULTRAPOR

DESMOFLEX

CARMYFIX

**REPI
FIX**

Why THRAKON?



Reliability

THRAKON is one of the most reliable producers of mortars in Greece with guaranteed steady supply and six production facilities.



Quality

We offer products, services and solutions of the highest quality which add value to our customers.



Responsibility

THRAKON, since its foundation, presents in market high quality products and integrated solutions, that are innovative, environmentally friendly and economically profitable for the industry. We operate a continuous and reliable business strategy for our clients in order to justify and maintain their trust in us.



Technical Support

THRAKON recognizing the importance of after sales services, is committed to provide complete solutions and advice from specialized engineers and experienced applicators. We want always be close to the customer with a high sense of responsibility.



MICROCEMENT DECOR

Primers for surface preparation

Microcement Systems

Microcement Protection

Floor Reinforcement

PRIMERS FOR SURFACE PREPARATION



GLX 292 FLEX PRIM

Acrylic primer - High penetration

Ready to use micronized acrylic water-based primer with high penetration ability.

- Ideal for preparing each new or old porous surface such as plaster, brick, concrete, plastered walls etc, creating an adhesion bridge for acrylic plasters, water paints, mortars, tile adhesives, acrylic and cementitious waterproofing spreads etc.
- Exterior & Interior use
- 15-20 m²/L depending on surface porosity
- 240 items (1 kg)
- 84 items (5 kg)
- 24 items (20 kg)
- 16 items (1 kg)

Code	Pkg
P21472920	1 kg
P21472925	5 kg
P21472921	20 kg



GLX 298 PREMIUM

Acrylic based primer for improving plaster adhesion strength

GLX 298 is ready to use acrylic based primer. Consists of synthetic resins and quartz sand.

- For improving adhesion strength of cement or gypsum based plaster on smooth or nonabsorbing surfaces. After the application, a rough surface is created.
- Exterior & Interior use
- 0,19 - 0,24 kg/m²
- Pink
- 160 items (1 kg)

Code	Pkg	Shade
P121479800	1 kg	Pink
P121472983	5 kg	
P121472984	20 kg	

MICROCEMENT SYSTEMS



DECOR FINE PLUS

Decorative coating in paste form

Acrylic based decorative coating for microcement. One-component, ready-to-use, for indoor or outdoor application.

- It is applied on horizontal or vertical surfaces from concrete, plaster, gypsum boards, cement boards, undersoil heating, existing ceramic tiles, etc. Ideal for small applications on sinks, bathtubs, stairs, etc.
- Exterior & Interior use
- 1,5 - 1,6 kg/m²/mm layer thickness
- Tinted according to the new CLIMAPLUS fan deck, in more than 500 shades. DECOR FINE PLUS can be tinted by the commercial network tinting machines.
- 1 - 7 days
- 80 items (5 kg)
- 36 items (15 kg)

Code	Pkg
P21901010	5 kg
P21901000	15 kg



DECOR

Microcement mortar – Two components

Microcement consisting of two components for creating colored decorative surfaces on floors and walls. Creates the traditional Greek Cycladic style with water formations. Applied at a thickness 2 - 3 mm, in a single layer on a solid and properly primed substrate. Combined with the reinforcing fiberglass mesh CLIMAPLUS. Suitable for indoors and outdoors spaces. Available in packs of 30kg (25kg A and 5kg B).

- Ideal for special applications such as counters, sinks, showers, pools, planters, stairs, etc. Colors: Available in white and 9 selected shades.
- Exterior & Interior use
- 1,5 kg/m²/mm layer thickness
- 48 items (25 kg)
- 72 items (5 kg)

Code	Pkg
T10002000	A Comp. 25 kg
P21901005	B Comp. 5 kg



DECOR ART

Color pigments in liquid form

Pigment in liquid form which is mixed with THRAKON DECOR. Also mixed with any type of cement such as plasters, sealants, adhesives, etc.

- Suitable for coloring microcement as well as plasters, sealants, repair, etc.
- THRAKON gives you the opportunity to choose more shades by choosing the tone you want from the color chart.
- 1 - 7 days

Code	Pkg
C/C	250 mL



DECOR SUPERIOR

3-component (epoxy) microcement

3-component, epoxy based, microcement for creating colored decorative surfaces on floors and walls. Creates the traditional Greek Cycladic style with various formations. Applied at a thickness 2 - 10mm, in a single layer on a solid and properly primed substrate. Combined with the reinforcing CLIMAPLUS fiberglass mesh. Suitable for indoors and outdoors applications.

- Ideal for applications in wet areas. Also ideal for areas with high movement because of the high strength.
- Exterior & Interior use
- 1,5 kg/m²/mm layer thickness
- 36 items (**A** 15kg + **B** 1kg + **Γ** 1kg)

Code	Pkg	
P11901015	17 kg / SET	A: 15 kg
P21901131		B: 1 kg
P21901130		C: 1 kg



DECOR ART SUPERIOR

Color pigments in liquid form for the DECOR SUPERIOR microcement system

Pigment in liquid form which is mixed with THRAKON DECOR SUPERIOR

- Suitable for coloring microcement as well as plasters, sealants, repair, etc.
- THRAKON gives you a choice of more SHADES by choosing the desired tone from the CLIMAPLUS fan deck.
- 1 - 7 days

Code	Pkg
C/C	250 mL

MICROCEMENT PROTECTION



DECOR PRIM
Impregnating primer for microcement

Micromolar primer water based high penetration, suitable for impregnating and stabilizing microcement before applying the final varnish.

- Suitable for application on any cementitious surface, such as microcement, traditional type screeds, plasters etc.
- Exterior & Interior use
- 0,1 - 0,15 kg/m² depending on the porosity of the substrate
- 16 Items (1 kg)

Code	Pkg
P21901001	1 kg



DECOR PROTECT
Water based varnish for protecting microcement

Specially formulated varnish to protect cementitious surfaces which have been treated with DECOR PRIM.

- Suitable for indoor and outdoor use on any kind of cementitious surface where there is no standing water, fats and oils.
- Exterior & Interior use
- 0,1 - 0,2 kg/m² depending on the porosity of the substrate
- 16 Items (1 kg)
- Transparent Glossy

Code	Pkg
P21901110	1 kg



DECOR PU VARNISH
Polyurethane varnish - Two components, for protecting microcement

Transparent polyurethane varnish, two components. It offers excellent waterproofing, high mechanical strength, resistance to chemical agents, protection against yellowing and UV radiation.

- Suitable for sealing and protecting any kind of structural element. Highly recommended for microcement, cementitious substrates, wood, metal, natural stone, etc. The special formula contains UV filters against UV radiation providing protection of shades and styles because it does not discolor or turn yellow over time.
- Exterior & Interior use
- 0,08 - 0,12 kg/m² depending on the porosity of the substrate
- 12 Items (1 kg)
- Glossy or Matte

Code	Pkg
P21901121	1 kg
P21901122	4 kg



ANTISLIP
Non-Slip varnish 2-component

Transparent, non-slip, 2-component varnish for indoor and outdoor use with strong adhesion, high resistance to abrasion and to chemical agents. It provides excellent waterproofing and protection to any kind of structural elements.

- It provides excellent waterproofing and protection to any kind of structural elements.
- Exterior & Interior use
- 80 - 120 gr/m²
- 6 items (1 kg [A+B Comp.])
6 items (4 kg [A+B Comp.])
- Transparent matte

Code	Pkg	Shade
P121901301	1 kg	Transparent/ Matte
P121901304	4 kg	

FLOOR REINFORCEMENT



CLIMAPLUS MESH (160 g/m²)
Anti-alkaline fiberglass mesh, produced under ETAG 004.

Suitable for the reinforcement of the basic layer of the exterior thermal insulation system CLIMAPLUS.

- Exterior use
- 1,1 m²/m
- 33 rolls
- 1m x 50m

Grid size: 4 x 4 mm

Code	m ² / Palette
T10320020	1650





ICON MEMO

-  Interior and exterior use
-  Exterior use
-  Interior use
-  Application
-  Delivery time
-  Dimensions
-  Weight
-  Consumption
-  Items per pallet
-  Items per box
-  Shades
-  Also provided in silo
-  Coefficient of thermal conductivity
- C/C** Where C/C appears, call us to provide you with the code of the product.

CERTIFICATIONS / SYSTEMS

- C1** With normal characteristics, for absorbent tiles and common substrates - Exterior & Interior use.
- C1T** With normal characteristics, for absorbent tiles and normal substrates - with zero vertical slip - Exterior & Interior use.
- C1TE** With normal characteristics for absorbent tiles and common substrates. With slip resistance and extended open time - Exterior & Interior use.
- C2T** With enhanced features for non-absorbent tiles and zero vertical slip - Exterior & Interior use.
- C2E** With enhanced features for non-absorbent tiles and extended open time - Exterior & Interior use.
- C2TE** With enhanced features for non-absorbent tiles, with zero vertical slip and extended open time - Elastic - Exterior & Interior use.
- CG2 WA** With enhanced features for demanding applications, with high abrasion resistance, low water absorption and low shrinkage - Exterior & Interior use.
- D2TE** Dispersion adhesive with enhanced characteristics for all types of tiles, with zero vertical slip and extended open time - Exterior & Interior use.
- R2T** Epoxy-based glue with reinforced characteristics for all types of tiles and with zero vertical slip - Exterior & Interior use.
- S1** With enhanced features for non-absorbent tiles, with zero vertical slip and extended open time - Very Elastic - Exterior & Interior use.
- S2** With enhanced features for non-absorbent tiles, with zero vertical slip and extended open time - Super Elastic - Exterior & Interior use.
- CE** The CE marking is the mark of product quality. Its existence ensures for the consumer that the characteristics of the product he has chosen correspond to the European characteristics established for the product.
-  EU Ecolabel for products that meet strict ecological criteria.
-  Fiber reinforced product
-  Fire protection class A2
-  Certification of the external thermal insulation system.
-  European Standard EN 13499 for the thermal insulation system.
-  Standard requirements for cementitious grouts.
-  Standard requirements for Expanded Polystyrene (EPS) according to the performance of the material in strength.
-  Harmonized standard for external and internal coatings.
-  A product that can be used in the CLIMA-PLUS external thermal insulation system.





Headquarters

130 Siggrou Avenue
Athens -11745
7th floor

Customer Service

☎ +30 210 36 33 512
✉ sales@thrakon.gr

Technical Support

☎ +30 210 36 33 512
✉ info@thrakon.gr

Join us at:



/ Thrakon.Greece



/ company/thrakon-group



/ thrakon.greece



/ THRAKONGreece

We build together.

www.thrakon.gr